

X-Maxx® (Model 77086-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

5106A	Bearings & Bushings Ball bearing, black rubber sealed (15x24x5mm) (2)	7775X	Wheels, wheelie bar, 6061-T6 aluminum (blue-anodized) (2)/ axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings (4)
108A	Ball Bearing, black rubber sealed (15x26x5) (2)	7775A	Wheels, wheelie bar, 6061-T6 aluminum (dark titanium-
5107A	Ball Bearing, black rubber sealed (17x26x5) (2)	IIISA	anodized) (2)/ axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4
196A	Ball bearing, black rubber sealed (20x32x7mm) (2)		ball bearings (4)
196X	Ball bearing, black rubber sealed, stainless (20x32x7mm) (2)	7775G	Wheels, wheelie bar, 6061-T6 aluminum (green-anodized) (2)/
106	Ball Bearing, blue rubber sealed (15x24x5) (2)	11130	axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings
611	Ball bearings (5x11x4mm) (2)		(4)
120A	5 (), ()	7775T	Wheels, wheelie bar, 6061-T6 aluminum (orange-anodized) (2)/
	Ball bearings, black rubber sealed (12x18x4mm) (2)	77751	axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings
180A	Ball bearings, black rubber sealed (6x13x5mm) (2)		(4)
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)	7775R	Wheels, wheelie bar, 6061-T6 aluminum (red-anodized) (2)/
116	Ball bearings, blue rubber sealed (5x11x4mm) (2)	IIII	axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings
	Body & Accessories		
745	_		(4)
715	Body mounts, front & rear/ 3x15mm BCS (1)/ 3x12mm shoulder		Cush Drive Components
	screw (2)/ 3x10mm flat-head machine screw (6)/ 3x15mm flat-head	7794	Cush drive key/ pin/ elastomer damper
740	machine screw (2)	7793X	Housing, cush drive (front & rear halves)
710	Body reinforcement set (fits #7711 body)	6442	Spur gear, 46-tooth (machined, hardened steel) (wide face, 1.0
713X	Body support, rear/ 3x15mm CS (2) / 3x15mm flat-head machine	0442	metric pitch)
	(2) (fits X-Maxx®)	6447R	• •
711	Body, X-Maxx® (clear, trimmed, requires painting)/ window		Spur gear, 46-tooth, steel (wide-face, 1.0 metric pitch)
	masks/ decal sheet	6443	Spur gear, 50-tooth (machined, hardened steel) (wide face, 1.0
811G	Body, X-Maxx®, green (painted, decals applied) (assembled with		metric pitch)
	front & rear body mounts, rear body support, and tailgate protector)	6448R	Spur gear, 50-tooth, steel (wide-face, 1.0 metric pitch)
811	Body, X-Maxx®, orange (painted, decals applied) (assembled with	6444	Spur gear, 54-tooth (machined, hardened steel) (wide face, 1.0
	front & rear body mounts, rear body support, and tailgate protector)		metric pitch)
711X	Body, X-Maxx®, ProGraphix® (graphics are printed, requires	6449X	Spur gear, 54-tooth, steel (1.0 metric pitch)
	paint & final color application)/ decal sheet	6449R	Spur gear, 54-tooth, steel (wide-face, 1.0 metric pitch)
'811R	Body, X-Maxx®, red (painted, decals applied) (assembled with front		Differential Components
• • • • • • • • • • • • • • • • • • • •	& rear body mounts, rear body support, and tailgate protector)		-
711T	Body, X-Maxx®, Rock n' Roll (painted, decals applied)	7781X	Carrier, differential (aluminum)/ (requires #7783X spider gear shaft
, , , , ,	(assembled with tailgate protector)	7781	Carrier, differential/ x-ring gaskets (2)/ ring gear gasket/
811X	· · · · · · · · · · · · · · · · · · ·		16X23.5X.5 TW
0117	Body, X-Maxx®, Solar Flare (painted, decals applied) (assembled	5136X	Differential oil kit (1 each: 10K, 30K, 50K weights)
	with front & rear body mounts, rear body support, and tailgate	7880	Differential, front, complete (fits X-Maxx® 8s or XRT®)
047	protector)	7881	Differential, rear, complete (fits X-Maxx® 8s or XRT®)
817	Skid plate, roof (body) (black)/ 3x15mm CS (4) (requires	7782	Gear set, differential (output gears (2)/ spider gears (4)/16X23.5X.5
	#7713X to mount)	1102	TW(2))
817X	Skid plate, roof (body) (blue)/ 3x15mm CS (4) (requires #7713X	5041	
	to mount)		Grease, premium high performance (20cc)
'817G	Skid plate, roof (body) (green)/ 3x15mm CS (4) (requires	7780	Housing, differential (front/rear)
	#7713X to mount)	7780-BLUE	Housing, differential (front/rear), 6061-T6 aluminum (blue-
'817T	Skid plate, roof (body) (orange)/ 3x15mm CS (4) (requires		anodized)
	#7713X to mount)	7780-GRAY	Housing, differential (front/rear), 6061-T6 aluminum (gray-
'817R	Skid plate, roof (body) (red)/ 3x15mm CS (4) (requires #7713X		anodized)
	to mount)	7780-GRN	Housing, differential (front/rear), 6061-T6 aluminum (green-
712	Tailgate protector/ 3x8mm flathead screw (4)		anodized)
	Bumpers & Skidplates	7780-ORNG	Housing, differential (front/rear), 6061-T6 aluminum (orange-
			anodized)
733	Bumper mount, front/ bumper support	7780-RED	Housing, differential (front/rear), 6061-T6 aluminum (red-
734	Bumper mount, rear/ bumper support		anodized)
735	Bumper, front	5040	Oil, differential (20M wt) (standard)
736	Bumper, rear	7790	Pinion gear, differential, 11-tooth (front) (heavy duty) (use with
745	Skidplate, center		#7792 35-tooth differential ring gear)
744	Skidplate, front (1), rear (1)/ rubber impact cushion (2)	7791	Pinion gear, differential, 11-tooth (rear) (heavy duty) (use with
•			#7792 35-tooth differential ring gear)
	Chassis & Attachments	7792	Ring gear, differential, 35-tooth (heavy duty) (use with #7790,
719	Battery hold-down (2)/ foam pad (2)	1132	#7791 11-tooth differential pinion gears)
718	Battery hold-down mounts, left (2)/ right (2)/ 3x18mm CS (4)	7783X	Spider gear shaft (2)/ spacers (4)/16x23.5x.5 stainless washer (2)
715	Body mounts, front & rear/ 3x15mm BCS (1)/ 3x12mm shoulder	1103/	(for #7781X aluminum differential carrier)
7.10	screw (2)/ 3x10mm flat-head machine screw (6)/ 3x15mm flat-head	7702	· ·
	machine screw (2)	7783	Spider gear shaft (2)/ spacers (4)/16X23.5X.5 TW (2)
			Driveline Components
724	· ·		-
724	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/	7794	Cush drive key/ nin/ elastomer damper
	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15 CS (4)	7794 7754¥	Cush drive key/ pin/ elastomer damper Drive cup (1)/ 3x8mm CS (for use only with #7750X driveshaft)
733	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15 CS (4) Bumper mount, front/ bumper support	7754X	Drive cup (1)/ 3x8mm CS (for use only with #7750X driveshaft)
733 734	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15 CS (4) Bumper mount, front/ bumper support Bumper mount, rear/ bumper support		Drive cup (1)/ 3x8mm CS (for use only with #7750X driveshaft) Drive cup, steel, extreme heavy duty (2)/ 3x8mm CS, heavy
733 734 735	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15 CS (4) Bumper mount, front/ bumper support Bumper mount, rear/ bumper support Bumper, front	7754X	Drive cup (1)/ 3x8mm CS (for use only with #7750X driveshaft) Drive cup, steel, extreme heavy duty (2)/ 3x8mm CS, heavy duty (2) (use only with #7750X driveshaft) (machined, heat
733 734 735 736	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15 CS (4) Bumper mount, front/ bumper support Bumper mount, rear/ bumper support	7754X 7754R	Drive cup (1)/ 3x8mm CS (for use only with #7750X driveshaft) Drive cup, steel, extreme heavy duty (2)/ 3x8mm CS, heavy duty (2) (use only with #7750X driveshaft) (machined, heat treated)
733 734 735 736	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15 CS (4) Bumper mount, front/ bumper support Bumper mount, rear/ bumper support Bumper, front	7754X 7754R 7755	Drive cup (1)/ 3x8mm CS (for use only with #7750X driveshaft) Drive cup, steel, extreme heavy duty (2)/ 3x8mm CS, heavy duty (2) (use only with #7750X driveshaft) (machined, heat treated) Driveshaft assembly, center, aluminum
733 734 735 736 722	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15 CS (4) Bumper mount, front/ bumper support Bumper mount, rear/ bumper support Bumper, front Bumper, rear	7754X 7754R	Drive cup (1)/ 3x8mm CS (for use only with #7750X driveshaft) Drive cup, steel, extreme heavy duty (2)/ 3x8mm CS, heavy duty (2) (use only with #7750X driveshaft) (machined, heat treated) Driveshaft assembly, center, aluminum Driveshaft, steel constant-velocity (heavy duty, shaft only, 160mm)
733 734 735 736 722 714X	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15 CS (4) Bumper mount, front/ bumper support Bumper mount, rear/ bumper support Bumper, front Bumper, rear Chassis Chassis top brace	7754X 7754R 7755	Drive cup (1)/ 3x8mm CS (for use only with #7750X driveshaft) Drive cup, steel, extreme heavy duty (2)/ 3x8mm CS, heavy duty (2) (use only with #7750X driveshaft) (machined, heat treated) Driveshaft assembly, center, aluminum
733 734 735 736 722 714X 723	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15 CS (4) Bumper mount, front/ bumper support Bumper mount, rear/ bumper support Bumper, front Bumper, rear Chassis Chassis top brace Nerf bars, chassis (2)	7754X 7754R 7755	Drive cup (1)/ 3x8mm CS (for use only with #7750X driveshaft) Drive cup, steel, extreme heavy duty (2)/ 3x8mm CS, heavy duty (2) (use only with #7750X driveshaft) (machined, heat treated) Driveshaft assembly, center, aluminum Driveshaft, steel constant-velocity (heavy duty, shaft only, 160mm)
733 734 735 736 722 714X 723 725	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15 CS (4) Bumper mount, front/ bumper support Bumper mount, rear/ bumper support Bumper, front Bumper, rear Chassis Chassis top brace Nerf bars, chassis (2) Seal kit, receiver box (includes o-ring, seals, and silicone grease)	7754X 7754R 7755	Drive cup (1)/ 3x8mm CS (for use only with #7750X driveshaft) Drive cup, steel, extreme heavy duty (2)/ 3x8mm CS, heavy duty (2) (use only with #7750X driveshaft) (machined, heat treated) Driveshaft assembly, center, aluminum Driveshaft, steel constant-velocity (heavy duty, shaft only, 160mm) (1) (replacing #7750 also requires #7751X, #7754X and #7768 or
733 734 735 736 722 714X 723 725	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15 CS (4) Bumper mount, front/ bumper support Bumper mount, rear/ bumper support Bumper, front Bumper, front Chassis Chassis Chassis top brace Nerf bars, chassis (2) Seal kit, receiver box (includes o-ring, seals, and silicone grease) Skidplate, center	7754X 7754R 7755 7750X	Drive cup (1)/ 3x8mm CS (for use only with #7750X driveshaft) Drive cup, steel, extreme heavy duty (2)/ 3x8mm CS, heavy duty (2) (use only with #7750X driveshaft) (machined, heat treated) Driveshaft assembly, center, aluminum Driveshaft, steel constant-velocity (heavy duty, shaft only, 160mm) (1) (replacing #7750 also requires #7751X, #7754X and #7768 or #7768R) Oil, differential (20M wt) (standard)
733 734 735 736 722 714X 723 725 745	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15 CS (4) Bumper mount, front/ bumper support Bumper mount, rear/ bumper support Bumper, front Bumper, front Bumper, rear Chassis Chassis top brace Nerf bars, chassis (2) Seal kit, receiver box (includes o-ring, seals, and silicone grease) Skidplate, center Skidplate, front (1), rear (1)/ rubber impact cushion (2)	7754X 7754R 7755 7750X	Drive cup (1)/ 3x8mm CS (for use only with #7750X driveshaft) Drive cup, steel, extreme heavy duty (2)/ 3x8mm CS, heavy duty (2) (use only with #7750X driveshaft) (machined, heat treated) Driveshaft assembly, center, aluminum Driveshaft, steel constant-velocity (heavy duty, shaft only, 160mm) (1) (replacing #7750 also requires #7751X, #7754X and #7768 or #7768R) Oil, differential (20M wt) (standard) Rebuild kit, steel constant-velocity driveshaft (includes pins for 2
733 734 735 736 722 714X 723 725 745 744	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15 CS (4) Bumper mount, front/ bumper support Bumper mount, rear/ bumper support Bumper, front Bumper, rear Chassis Chassis top brace Nerf bars, chassis (2) Seal kit, receiver box (includes o-ring, seals, and silicone grease) Skidplate, center Skidplate, front (1), rear (1)/ rubber impact cushion (2) Spacer, battery compartment (2)/ foam blocks (4)/ foam pad (2)	7754X 7754R 7755 7750X 5040 7751X	Drive cup (1)/ 3x8mm CS (for use only with #7750X driveshaft) Drive cup, steel, extreme heavy duty (2)/ 3x8mm CS, heavy duty (2) (use only with #7750X driveshaft) (machined, heat treated) Driveshaft assembly, center, aluminum Driveshaft, steel constant-velocity (heavy duty, shaft only, 160mm) (1) (replacing #7750 also requires #7751X, #7754X and #7768 or #7768R) Oil, differential (20M wt) (standard) Rebuild kit, steel constant-velocity driveshaft (includes pins for 2 driveshaft assemblies (for use only with #7750X driveshaft)
7724 7733 7734 7735 736 722 7714X 7723 7725 7745 7744 7717X	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15 CS (4) Bumper mount, front/ bumper support Bumper mount, rear/ bumper support Bumper, front Bumper, front Bumper, rear Chassis Chassis top brace Nerf bars, chassis (2) Seal kit, receiver box (includes o-ring, seals, and silicone grease) Skidplate, center Skidplate, front (1), rear (1)/ rubber impact cushion (2) Spacer, battery compartment (2)/ foam blocks (4)/ foam pad (2) Tires, rubber (2) (fits Traxxas® #7775X wheelie bar wheels)	7754X 7754R 7755 7750X 5040 7751X 7836-BLUE	Drive cup (1)/ 3x8mm CS (for use only with #7750X driveshaft) Drive cup, steel, extreme heavy duty (2)/ 3x8mm CS, heavy duty (2) (use only with #7750X driveshaft) (machined, heat treated) Driveshaft assembly, center, aluminum Driveshaft, steel constant-velocity (heavy duty, shaft only, 160mm) (1) (replacing #7750 also requires #7751X, #7754X and #7768 or #7768R) Oil, differential (20M wt) (standard) Rebuild kit, steel constant-velocity driveshaft (includes pins for 2 driveshaft assemblies (for use only with #7750X driveshaft) Steering blocks, 6061-T6 aluminum (blue-anodized), left & righ
733 734 735 736 722 714X 723 725 745 744	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15 CS (4) Bumper mount, front/ bumper support Bumper mount, rear/ bumper support Bumper, front Bumper, rear Chassis Chassis top brace Nerf bars, chassis (2) Seal kit, receiver box (includes o-ring, seals, and silicone grease) Skidplate, center Skidplate, front (1), rear (1)/ rubber impact cushion (2) Spacer, battery compartment (2)/ foam blocks (4)/ foam pad (2)	7754X 7754R 7755 7750X 5040 7751X	Drive cup (1)/ 3x8mm CS (for use only with #7750X driveshaft) Drive cup, steel, extreme heavy duty (2)/ 3x8mm CS, heavy duty (2) (use only with #7750X driveshaft) (machined, heat treated) Driveshaft assembly, center, aluminum Driveshaft, steel constant-velocity (heavy duty, shaft only, 160mm) (1) (replacing #7750 also requires #7751X, #7754X and #7768 or #7768R) Oil, differential (20M wt) (standard) Rebuild kit, steel constant-velocity driveshaft (includes pins for 2 driveshaft assemblies (for use only with #7750X driveshaft)

Page 2	X-Maxx®: TQi™ Traxxas Link™ Enabled 2.4GHz R	ladio & TS	M® (Model 77086-4) Parts List
7836-GRN	Steering blocks, 6061-T6 aluminum (green-anodized), left & right	7830	Suspension arm, black, lower (right, fron
7936 OPNG	5 ·	7921Y	Suspension arm blue lower (left front o

	right
7836-ORNG	Steering blocks, 6061-T6 aluminum (orange-anodized), left & right
7836-RED	Steering blocks, 6061-T6 aluminum (red-anodized), left & right
7836	Steering blocks, left & right
7737X	Steering blocks, left & right (requires 20x32x7 ball bearings)
7836X	Steering blocks, left & right/ caster blocks (c-hubs), left & right/ 20x32x7mm bearings (2)/ 15x24x5mm bearings (2)
7768A	Stub axle, aluminum (black-anodized) (1) (for use only with #7750X or 7896 driveshaft)
7768	Stub axle, aluminum, (blue-anodized) (1) (for use only with #7750X or 7896 driveshaft)
7768G	Stub axle, aluminum, (green-anodized) (1) (for use only with #7750X or 7896 driveshaft)
7768T	Stub axle, aluminum, (orange-anodized) (1) (for use only with #7750X or 7896 driveshaft)
7768R	Stub axle, aluminum, (red-anodized) (1) (for use only with #7750X or 7896 driveshaft)
7758A	Wheel nuts, splined, 17mm, serrated (black-anodized) (4)
7758	Wheel nuts, splined, 17mm, serrated (blue-anodized) (4)
7758G	Wheel nuts, splined, 17mm, serrated (green-anodized) (4)

Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Front Suspension & Steering

Wheel nuts, splined, 17mm, serrated (orange-anodized) (4)

7726	Bulkhead tie bar, upper (1)/ lower (2) (steel)
7721	Bulkhead, front (lower)
7720X	Bulkhead, front (upper)

7758T

7758R

Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left 7832-BLUE & riaht

7832-GRAY Caster blocks (c-hubs), 6061-T6 aluminum (gray-anodized), left & right

7832-GRN Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right

7832-ORNG Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right

7832-RED Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right

7732 Caster blocks (c-hubs), left & right 7832 Caster blocks (c-hubs), left & right 7879-BI UF Drag link, 6061-T6 aluminum (blue-anodized)

7879-GRAY Drag link, 6061-T6 aluminum (gray-anodized) 7879-GRN Drag link, 6061-T6 aluminum (green-anodized) 7879-ORNG Drag link, 6061-T6 aluminum (orange-anodized) 7879-RED Drag link, 6061-T6 aluminum (red-anodized)

7716 Mount, tie bar, front (1)/ rear (1) 7747-BLUE Servo horn, steering, 6061-T6 aluminum (blue-anodized) 7747-GRAY Servo horn, steering, 6061-T6 aluminum (gray-anodized) 7747-GRN Servo horn, steering, 6061-T6 aluminum (green-anodized) 7747-ORNG Servo horn, steering, 6061-T6 aluminum (orange-anodized)

7747-RED Servo horn, steering, 6061-T6 aluminum (red-anodized) 7747 Servo horn, steering/linkage, steering (46mm, assembled with pivot balls)

7739 Shock tower, front (left & right halves)

7746-BLUE Steering bellcranks (left & right)/ draglink (6061-T6 aluminum, blue-anodized) (fits X-Maxx®)

7746-GRAY Steering bellcranks (left & right)/ draglink (6061-T6 aluminum, gray-anodized) (fits X-Maxx®)

7746-GRN Steering bellcranks (left & right)/ draglink (6061-T6 aluminum, green-anodized) (fits X-Maxx®)

Steering bellcranks (left & right)/ draglink (6061-T6 aluminum, 7746-ORNG orange-anodized) (fits X-Maxx®)

7746-RED Steering bellcranks (left & right)/ draglink (6061-T6 aluminum, red-anodized) (fits X-Maxx®) 7746 Steering bellcranks/ bellcrank support/servo saver/ servo saver

spring/ draglink/ 3x20mm shoulder screws (2) 7836-BLUE Steering blocks, 6061-T6 aluminum (blue-anodized), left & right

7836-GRAY Steering blocks, 6061-T6 aluminum (gray-anodized), left & right 7836-GRN

Steering blocks, 6061-T6 aluminum (green-anodized), left & right

7836-ORNG Steering blocks, 6061-T6 aluminum (orange-anodized), left & right

7836-RED Steering blocks, 6061-T6 aluminum (red-anodized), left & right 7836 Steering blocks, left & right

7737X Steering blocks, left & right (requires 20x32x7 ball bearings) 7836X Steering blocks, left & right/ caster blocks (c-hubs), left & right/ 20x32x7mm bearings (2)/ 15x24x5mm bearings (2)

7746X Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo)

7831 Suspension arm, black, lower (left, front or rear), heavy duty (1)

nt or rear), heavy duty

Suspension arm, blue, lower (left, front or rear), heavy duty (1)

7830X Suspension arm, blue, lower (right, front or rear), heavy duty

Suspension arm, green, lower (left, front or rear), heavy duty 7831G (1)

Suspension arm, green, lower (right, front or rear), heavy duty 7830G

Suspension arm, lower (left, front or rear) (1) 7730 Suspension arm, lower (right, front or rear) (1)

7831T Suspension arm, orange, lower (left, front or rear), heavy duty

7830T Suspension arm, orange, lower (right, front or rear), heavy duty (1)

7831R Suspension arm, red, lower (left, front or rear), heavy duty (1) 7830R Suspension arm, red, lower (right, front or rear), heavy duty (1) 7729 Suspension arm, upper (left or right, front or rear) (2)

Suspension arms, black, upper (left or right, front or rear), 7829 heavy duty (2)

7829X Suspension arms, blue, upper (left or right, front or rear), heavy duty (2)

7829G Suspension arms, green, upper (left or right, front or rear), heavy duty (2)

7829T Suspension arms, orange, upper (left or right, front or rear), heavy duty (2)

7829R Suspension arms, red, upper (left or right, front or rear), heavy duty (2)

7743 Suspension pin retainer (4)

Suspension pin retainer, 6061-T6 aluminum (blue-anodized) (4) 7743-BLUE 7743-GRAY Suspension pin retainer, 6061-T6 aluminum (gray-anodized) (4) 7743-GRN Suspension pin retainer, 6061-T6 aluminum (green-anodized)

7743-ORNG Suspension pin retainer, 6061-T6 aluminum (orange-anodized)

7743-RED Suspension pin retainer, 6061-T6 aluminum (red-anodized) (4) 7740 Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set)

7742 Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2)

7741 Suspension pins, 4x85mm (hardened steel) (2)

	Hardware
4859	CS 3x10 flathead (hex drive)
2584	Head screws, 3x12mm cap-head machine (hex drive) (6) (TRX®
	2.5, 2.5R, 3.3)
4955	Pins, axle (2.5x12mm) (4)
4857	Screw, 3x20 countersunk machine (hex drive) (6)
3234	Screws, 2.5x14mm cap-head machine (hex drive) (6)
2577	Screws, 3x10mm button-head machine (hex drive) (6)
2587	Screws, 3x10mm caphead machine (6) (no washer)
2593	Screws, 3x14mm button-head machine (hex drive) (6)
2579	Screws, 3x15mm button-head machine (hex drive) (6)
2586	Screws, 3x15mm cap-head machine (hex drive) (6)
3646	Screws, 3x15mm flat-head machine (hex drive) (6)
2585	Screws, 3x20mm cap-head machine (hex drive) (6)
2581	Screws, 3x25mm button-head machine (hex drive) (6)
2575	Screws, 3x6mm button-head machine (hex drive) (6)
2576	Screws, 3x8mm button-head machine (hex drive) (6)
2535	Screws, 4x10mm countersunk machine (hex drive) (6)
3937	Screws, 4x12mm button-head machine (hex drive) (6)
3938	Screws, 4x14mm button-head machine (hex drive) (6)
2594	Screws, 4x15mm button-head machine (hex drive) (6)
2546	Screws, 4x15mm countersunk machine (hex drive) (6)
3933	Screws, 4x16mm button-head machine (hex drive) (6)

Wheel wrench, splined, 17mm **ED Lights**

Screws, set (grub), 4mm (with heavy duty threadlock) (6)

Screws, 4x22mm button-head machine (hex drive) (6)

Screws, 4x25mm button-head machine (hex drive) (6)

Screws, 4x30mm button-head machine (hex drive) (6)

Screws, 4x35mm button-head machine (hex drive) (6)

Shoulder screws, Ultra Shocks (3x12 hex drive) (6)

Extension harness, LED lights (high-voltage) 7882 6590

Set (grub) screws, 3mm hardened (12)

High-Voltage Power Amplifier

2597

2596

2598X

2595

4897X

2743

3642X

5480X

LED light bar, front (high-voltage) (40 white LEDs (double row), 7884 82mm wide) (fits Maxx®, X-Maxx®, or XRT™)

Page 3	X-Maxx®:	TQi™ Traxxas Link™	¹ Enabled 2.4GHz Radio	o & TSM® (Model 77086-4) Par	ts List
--------	----------	--------------------	-----------------------------------	------------------------------	---------

	LED light bar, rear, red (with white reverse light) (high-voltage) (24 red LEDs, 24 white LEDs, 100mm wide)/ light bar mount	2968X	LiPo cell voltage checker/balancer (includes #2938X adapter for Traxxas® iD® batteries)
7885	(fits Maxx®, X-Maxx®, or XRT™) LED light kit, complete (includes #6590 high-voltage power	2968	LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries)
	amplifier)	6533	Receiver, micro, TQi 2.4GHz with telemetry & TSM® (5-channel)
	Motors & Electronics	6552	Seal kit, expander box (includes o-ring, seals, and silicone grease)
749	Adapter, standard servo (adapts standard servo to fit in X-	6526	Sensor, auto-detectable, temperature
	Maxx®)Adapter, standard servo (adapts standard servo to fit in	6527	Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage
	Maxx®, X-Maxx®, or XRT®)	6531	Sensor, temperature & voltage (fits X-Maxx® or XRT®)
3475	Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s)	6521	Sensor, temperature and voltage (long)
787-BLUE	Cover, gear (blue-anodized 6061-T6 aluminum)	2086	Servo case/gaskets (for 2085 & 2085X servos)
787-GRAY	Cover, gear (gray-anodized 6061-T6 aluminum)	2085	Servo, digital high-torque (ball bearing), waterproof
787-GRN	Cover, gear (green-anodized 6061-T6 aluminum)	2085X	Servo, digital high-torque, metal gear (ball bearing),
	Cover, gear (orange-anodized 6061-T6 aluminum)		waterproof/ servo saver spring/ steering link
787-RED	Cover, gear (red-anodized 6061-T6 aluminum)	6553X	Telemetry Expander 2.0 and GPS module 2.0, TQi radio syste
3474	Dual cooling fan kit (with shroud), Velineon® 1200XL motor	6550X	Telemetry expander 2.0, TQi radio system (for use only with
2087 2 087X	Gear set (for 2085 servo)		#6551X GPS module)
362	Gear set, metal (for 2085, 2085X servos) Heat sink, Velineon® 1200XL	6551X	Telemetry GPS module 2.0, TQi radio system (for use only w
760	Motor mounts (front and rear)/ pins (2)		#6550X telemetry expander)
760-BLUE	Motor mounts, 6061-T6 aluminum (blue-anodized) (front &	6509R	TQi 2.4 GHz High Output radio system, 2-channel, Traxxas® Linle enabled, TSM® (2-ch transmitter, 5-ch micro receiver)
	rear)	6507R	TQi 2.4 GHz High Output radio system, 4-channel with
760-GRAY	Motor mounts, 6061-T6 aluminum (gray-anodized) (front & rear)	0307K	Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, the micro receiver)
760-GRN	Motor mounts, 6061-T6 aluminum (green-anodized) (front &	6528	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2-
	rear)	0320	channel (transmitter only)
760-ORNG	Motor mounts, 6061-T6 aluminum (orange-anodized) (front & rear)	6529	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output 3-channel (transmitter only)
760-RED	Motor mounts, 6061-T6 aluminum (red-anodized) (front & rear)	6530	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output
491	Motor, Velineon® 1200XL, brushless		4-channel (transmitter only)
3492	Rebuild kit, Velineon® 1200XL (includes plastic endbells (2),	6511	Traxxas® Link Bluetooth® module
	6x17x6mm ball bearings (2), 6x8x.3 washer (1), 6x8x1 washer (1), 7x6x12 spacer (1))		Ready-To-Race Model
.086	Servo case/gaskets (for 2085 & 2085X servos)	77086-4	X-Maxx®: Brushless Electric Monster Truck with TQi™ Traxxas
.085	Servo, digital high-torque (ball bearing), waterproof	77000 1	Link™ Enabled 2.4GHz Radio System & Traxxas Stability
.085X	Servo, digital high-torque, metal gear (ball bearing),		Management (TSM)®
00071	waterproof/ servo saver spring/ steering link		Rear Suspension
'878X	Spacer, motor shaft (steel)/ e-clip (1)	7700	-
496T	Velineon® VXL-8s Electronic Speed Control, waterproof	7726	Bulkhead tie bar, upper (1)/ lower (2) (steel)
	(brushless) (fwd/rev/brake)	7727X	Bulkhead, rear (upper & lower), center differential (replacing #772
759	Washers, motor mount, aluminum (blue-anodized) (4)/ 4x18mm	7727R	& #7728 requires #5108 ball bearings (2)) Bulkhead, rear (upper) (fits X-Maxx® 8s or XRT®)
	BCS (4)	7852-BLUE	Carriers, stub axle (blue-anodized 6061-T6 aluminum) (left &
759G	Washers, motor mount, aluminum (green-anodized) (4)/	7032-BLUL	right)
759R	4x18mm BCS (4) Washers, motor mount, aluminum (red-anodized) (4)/ 4x18mm	7852-GRAY	Carriers, stub axle (gray-anodized 6061-T6 aluminum) (left &
	BCS (4)	7852-GRN	right) Carriers, stub axle (green-anodized 6061-T6 aluminum) (left a
	Radio System, Batteries & Chargers	7002-0111	right)
872X	5000mah 11.1v 3-Cell 25C LiPo Battery	7752X	Carriers, stub axle (left & right) (requires 20x32x7 ball bearings)
889X	5000mah 14.8v 4-Cell 25C LiPo Battery (long)	7852-ORNG	Carriers, stub axle (orange-anodized 6061-T6 aluminum) (left
857X	6400mah 11.1v 3-Cell 25C LiPo Battery		right)
890X	6700mah 14.8v 4-Cell 25C LiPo Battery	7852	Carriers, stub axle (rear) (left & right)
914	AA 4PK	7852X	Carriers, stub axle (rear) (left & right)/ 20x32x7mm bearings (
938X	Adapter, Traxxas® iD® LiPo battery (adapts Traxxas® iD®		15x24x5mm bearings (2)
	batteries to separate balance ports)	7852-RED	Carriers, stub axle (red-anodized 6061-T6 aluminum) (left &
943	Battery charge indicators, green (4), grey (4), blue (4)		right)
548	Battery door, TQ 2.4 transmitter (replacement for #6516, 6517	7716	Mount, tie bar, front (1)/ rear (1)
	transmitter)	7738	Shock tower, rear (left & right halves)
990	Battery/charger completer pack (includes #2972 Dual iD	7831	Suspension arm, black, lower (left, front or rear), heavy duty
	charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery	7830	(1) Suspension arm, black, lower (right, front or rear), heavy du
007	(2)) Rattery/obarger completer neck (includes #2972 Duel iD	1000	(1)
997	Battery/charger completer pack (includes #2973 Dual iD charger (1), #2890X 6700mAh 14.8V 4-cell 25C LiPo iD® Battery	7831X	Suspension arm, blue, lower (left, front or rear), heavy duty (
972	(2)) Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery	7830X	Suspension arm, blue, lower (right, front or rear), heavy duty
.512	Identification		(1)
973	Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification	7831G	Suspension arm, green, lower (left, front or rear), heavy duty (1)
970	Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery	7830G	Suspension arm, green, lower (right, front or rear), heavy du
074	Identification	7731	(1) Suspension arm lower (left front or rear) (1)
971	Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto	7731 7730	Suspension arm, lower (left, front or rear) (1)
981	Battery Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto	7730 7831T	Suspension arm, lower (right, front or rear) (1) Suspension arm, orange, lower (left, front or rear), heavy du
.70 I	Battery Identification	70011	(1)
525	Communication link, telemetry expander	7830T	Suspension arm, orange, lower (right, front or rear), heavy
565	Data link, telemetry expander (connects #6550X telemetry	- • •	duty (1)
-00	expander 2.0 to the #6590 high-voltage power amplifier)	7831R	Suspension arm, red, lower (left, front or rear), heavy duty (1)
566	Data link, telemetry expander (connects #6550X telemetry	7830R	Suspension arm, red, lower (right, front or rear), heavy duty
	expander 2.0 to the Velineon® #3465 VXL-4s, #3485 Velineon®	7729	Suspension arm, upper (left or right, front or rear) (2)
			, , , , , , , , , , , , , , , , , , , ,
	VXL-6s, or #3496 Velineon® VXL-8s electronic speed control)	7829	Suspension arms, black, upper (left or right, front or rear),
087	Gear set (for 2085 servo)	7829	Suspension arms, black, upper (left or right, front or rear), heavy duty (2)
087 087X		7829	

7829X	Suspension arms, blue, upper (left or right, front or rear),	7856	Springs, shock (natural finish) (GTX) (1.346 rate, blue stripe)
7829G	heavy duty (2) Suspension arms, green, upper (left or right, front or rear),	7857	(2) Springs, shock (natural finish) (GTX) (1.450 rate, black stripe)
7829T	heavy duty (2) Suspension arms, orange, upper (left or right, front or rear),	7858	(2) Springs, shock (natural finish) (GTX) (1.538 rate, red stripe) (2
7829R	heavy duty (2) Suspension arms, red, upper (left or right, front or rear), heavy		Spur Gears & Pinion Gears
	duty (2)	6484X	Gear, 11-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
743 743-BLUE	Suspension pin retainer (4) Suspension pin retainer, 6061-T6 aluminum (blue-anodized) (4)	6485X	Gear, 12-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
743-GRAY 743-GRN	Suspension pin retainer, 6061-T6 aluminum (gray-anodized) (4)	6486X	(for use only with steel spur gears) Gear, 13-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
	Suspension pin retainer, 6061-T6 aluminum (green-anodized) (4)	6488X	(for use only with steel spur gears) Gear, 14-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
743-ORNG	Suspension pin retainer, 6061-T6 aluminum (orange-anodized) (4)		(for use only with steel spur gears)
743-RED 7740	Suspension pin retainer, 6061-T6 aluminum (red-anodized) (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm	6487X	Gear, 15-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
740	(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete	6489X	Gear, 16-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
742	set) Suspension pin set, shock mount (front or rear, hardened steel),	6490X	Gear, 17-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
7741	4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2)	6491R	Gear, 18-T pinion (machined) (1.0 metric pitch) (fits 5mm
	Shock Oil	6491X	shaft)/ set screw (for use only with steel spur gears) Gear, 18-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for
5031	Oil, shock (20 wt, 200 cSt, 60cc) (silicone)	6494X	use only with steel spur gears) Gear, 20-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
5032 5033	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone)	0-70 -7 /\	(for use only with steel spur gears)
5034	Oil, shock (50 wt, 600 cSt, 60cc) (silicone)	6494R	Gear, 20-T pinion (machined, hardened steel) (1.0 metric pitch (fits 5mm shaft)/ set screw
5035 5036	Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone)	6495X	Gear, 22-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
5037	Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone)	6496X	(for use only with steel spur gears) Gear, 24-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
5029 5038X	Shock oil bottle (60cc) (for mixing shock oil) Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt,	04307	(for use only with steel spur gears)
	& 80 wt premium shock oils with spinning carousel rack)	6442	Spur gear, 46-tooth (machined, hardened steel) (wide face, 1.0 metric pitch)
6038	Spinning carousel rack Shocks (GTX)	6447R	Spur gear, 46-tooth, steel (wide-face, 1.0 metric pitch)
765A		6443	Spur gear, 50-tooth (machined, hardened steel) (wide face, 1.0 metric pitch)
765 A 765	Body, GTX shock (aluminum, black-anodized) (1) Body, GTX shock (aluminum, blue-anodized) (1)	6448R	Spur gear, 50-tooth, steel (wide-face, 1.0 metric pitch)
765G	Body, GTX shock (aluminum, green-anodized) (1)	6444	Spur gear, 54-tooth (machined, hardened steel) (wide face, 1.6
765X	Body, GTX shock (aluminum, hard-anodized, PTFE-coated) (1)	6449X	metric pitch) Spur gear, 54-tooth, steel (1.0 metric pitch)
7765T	Body, GTX shock (aluminum, orange-anodized) (1)	6449A	Spur gear, 54-tooth, steel (wide-face, 1.0 metric pitch)
765R 762X	Body, GTX shock (aluminum, red-anodized) (1) Rebuild kit, GTX shocks (lower cartridge, assembled, pistons,		Steering Components
	piston nuts, bladders) (renews 2 shocks)	5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
763T	Shaft, GTX shock TiN-coated (2) (assembled with rod ends and steel hollow balls)	5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
764A	Shock caps, aluminum (blue-anodized), GTX shocks (4)/	7879-BLUE	Drag link, 6061-T6 aluminum (blue-anodized)
	spacers (8)	7879-GRAY 7879-GRN	Drag link, 6061-T6 aluminum (gray-anodized) Drag link, 6061-T6 aluminum (green-anodized)
764G	Shock caps, aluminum (green-anodized), GTX shocks (4)/	7879-ORNG	Drag link, 6061-T6 aluminum (green-anodized)
764X	spacers (8) Shock caps, aluminum (hard anodized, PTFE-coated), GTX	7879-RED	Drag link, 6061-T6 aluminum (red-anodized)
10-170	shocks (4)/ spacers (8)	7747-BLUE	Servo horn, steering, 6061-T6 aluminum (blue-anodized)
764R	Shock caps, aluminum (red-anodized), GTX shocks (4)/	7747-GRAY	Servo horn, steering, 6061-T6 aluminum (gray-anodized)
7764	spacers (8) Shock and CTV chacks/apring parch/adjusters/3.5x14.CS (3)	7747-GRN 7747-ORNG	Servo horn, steering, 6061-T6 aluminum (green-anodized) Servo horn, steering, 6061-T6 aluminum (orange-anodized)
764	Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14 CS (2) (for 2 shocks)	7747-RED	Servo horn, steering, 6061-T6 aluminum (red-anodized)
763	Shock shafts, GTX, 110mm (assembled with rod ends & hollow balls) (steel, chrome finish) (2)	7747	Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls)
761A	Shocks, GTX, aluminum (black-anodized) (fully assembled w/o	7746-BLUE	Steering bellcranks (left & right)/ draglink (6061-T6 aluminum
761	springs) (2) Shocks, GTX, aluminum, blue-anodized (fully assembled w/o	7746-GRAY	blue-anodized) (fits X-Maxx®) Steering bellcranks (left & right)/ draglink (6061-T6 aluminum
761G	springs) (2) Shocks, GTX, aluminum, green-anodized (fully assembled w/o	7746-GRN	gray-anodized) (fits X-Maxx®) Steering bellcranks (left & right)/ draglink (6061-T6 aluminum
761T	springs) (2) Shocks, GTX, aluminum, orange-anodized (fully assembled	7746-ORNG	green-anodized) (fits X-Maxx®) Steering bellcranks (left & right)/ draglink (6061-T6 aluminum
761R	w/o springs) (2) Shocks, GTX, aluminum, red-anodized (fully assembled w/o	7746-RED	orange-anodized) (fits X-Maxx®) Steering bellcranks (left & right)/ draglink (6061-T6 aluminum
767	springs) (2) Spring retainer (adjuster), blue-anodized aluminum, GTX	7746	red-anodized) (fits X-Maxx®) Steering bellcranks/ bellcrank support/servo saver/ servo saver
	shocks (4) (assembled with o-ring)		spring/ draglink/ 3x20mm shoulder screws (2)
767G	Spring retainer (adjuster), green-anodized aluminum, GTX shocks (4) (assembled with o-ring)	7746X	Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo)
767X	Spring retainer (adjuster), PTFE-coated aluminum, GTX shocks (4) (assembled with o-ring)	7748	Toe links, molded composite, 173mm (158mm center to center) (black) (2)
767R	Spring retainer (adjuster), red-anodized aluminum, GTX	7748X	Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum
7853	shocks (4) (assembled with o-ring) Springs, shock (natural finish) (GTX) (0.824 rate, white stripe)		stronger than titanium) (157mm) (2)/ rod ends, assembled wit steel hollow balls (4)/ aluminum wrench, 10mm (1)
854	(2) Springs, shock (natural finish) (GTX) (0.929 rate, orange stripe)	7748G	Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends,
	(2)		assembled with steel hollow balls (4)/ aluminum wrench,
	\ - /		10mm (1)

7748R			
	Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with	7700	Transmission Components
	steel hollow balls (4)/ aluminum wrench, 10mm (1)	7796	Center drive, torque biasing (assembled)/ 17x26x5 ball bearings (2) (requires #7727X bulkheads)
	Suspension Linkage	7787-BLUE	Cover, gear (blue-anodized 6061-T6 aluminum)
7798	Insert, threaded steel (replacement inserts for #7748G, 7748R,	7787-GRAY	Cover, gear (gray-anodized 6061-T6 aluminum)
	7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1)	7787-GRN	Cover, gear (green-anodized 6061-T6 aluminum)
	right threaded insert)	7787-ORNG	Cover, gear (orange-anodized 6061-T6 aluminum)
7797	Rod ends (4) (assembled with steel pivot balls) (replacement	7787-RED	Cover, gear (red-anodized 6061-T6 aluminum)
77.40	ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X)	7785X	Input gear, transmission, 20-tooth/ 2.5x12mm pin
7743	Suspension pin retainer (4)	7786X	Input shaft, transmission (cush drive)
7743-BLUE	Suspension pin retainer, 6061-T6 aluminum (blue-anodized) (4)	5040	Oil, differential (20M wt) (standard)
7743-GRAY 7743-GRN	Suspension pin retainer, 6061-T6 aluminum (gray-anodized) (4) Suspension pin retainer, 6061-T6 aluminum (green-anodized)	7784X	Output gear, 51-tooth, metal (requires #7785X input gear)
7743-GRN	(4)		Traxxas Tools
7743-ORNG		3433X	Body reamer (aluminum handle)
7740 011110	(4)	3433	Body reamer (plastic handle)
7743-RED	Suspension pin retainer, 6061-T6 aluminum (red-anodized) (4)	3436	Cap, body reamer
7740	Suspension pin set, front or rear corner (hardened steel), 4x85mm	3432	Scissors, curved tip
	(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete	3431	Scissors, straight tip
	set)	8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes
7742	Suspension pin set, shock mount (front or rear, hardened steel),		premium handle (medium), travel pouch, hex drivers (straight:
	4x25mm (2), 4x38mm (2)		1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm,
7741	Suspension pins, 4x85mm (hardened steel) (2)		and 8.0mm), 1/4" drive
7748	Toe links, molded composite, 173mm (158mm center to center)	8720	Speed bit handle, large (overmolded)
77.40V	(black) (2)	8721	Speed bit handle, medium (one piece)
7748X	Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum,	8722	Speed bit handle, premium (rubber overmold)
	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)	8710	Speed Bit Master Set, hex and nut driver, 13-piece, includes
7748G	Toe links, X-Maxx® (TUBES green-anodized, 7075-T6		premium handle (medium), travel pouch, hex drivers (straight:
77400	aluminum, stronger than titanium) (157mm) (2)/ rod ends,		1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm, 3.0mm), and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm,
	assembled with steel hollow balls (4)/ aluminum wrench,		7.0mm, 8.0mm), 1/4" drive
	10mm (1)	8711	Speed Bit Master Set, hex driver, 7-piece straight and ball end,
7748R	Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum,	0711	includes premium handle (medium), travel pouch, hex drivers
	stronger than titanium) (157mm) (2)/ rod ends, assembled with		(straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm,
	steel hollow balls (4)/ aluminum wrench, 10mm (1)		2.5mm, 3.0mm), 1/4" drive
	Team Traxxas Items	8719	Speed Bit Master Set, nut driver, 6-piece, includes premium
2514			handle (medium), travel pouch, and nut drivers (4.0mm,
9950	Decal sheet, racing sponsors		4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
9909	Official Team Traxxas® racing decal set(flag logo/ 6-color) Traxxas® racing banner, red & black (3x7 feet)	8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm),
9909			1/4" drive
	Tires & Wheels	8716X	Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm,
7772A	Tires & wheels, assembled, glued (X-Maxx® black chrome	0715	3.0mm) 1/4" drive
	wheels, Maxx® AT tires, foam inserts) (left & right) (2)	8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm, 2.5mm), 1/4" drive
7774A	Tires & wheels, assembled, glued (X-Maxx® black chrome	8715X	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm,
	wheels, Sledgehammer® tires, foam inserts) (left & right) (2)	0713X	2.5mm, 3.0mm), 1/4" drive
7772X	Tires & wheels, assembled, glued (X-Maxx® black wheels, Maxx®	0744	2.011111, 0.0111111, 174 01110
1112/		0/14	Speed Bit Set, screwdriver, 3-piece straight (3mm slotted, #1
	AT tires, foam inserts) (left & right) (2)	8714	Speed Bit Set, screwdriver, 3-piece straight (3mm slotted, #1 Phillips, and #2 Phillips bits). 1/4" drive
	Tires & wheels, assembled, glued (X-Maxx® black wheels,	6714 2748R	Phillips, and #2 Phillips bits), 1/4" drive
7773	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2)		
7773	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels,		Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench /
7773 7772G	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2)		Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U- joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm,
	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels,	2748R	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U- joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut
7773 7772G 7774G	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2)	2748R	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U- joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00
7773 7772G 7774G	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels,	2748R	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and
7773 7772G 7774G 7772T	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2)	2748R 3415	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle)
7773 7772G 7774G 7772T	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2)	2748R	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U- joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm
7773 7772G 7774G 7772T 7774T	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels,	2748R 3415	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle)
7773 7772G	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2)	2748R 3415 5480X	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TUITINGERS & TITERER ROSS
7773 7772G 7774G 7772T 7774T 7772R	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels,	2748R 3415	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U- joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm
7773 7772G 7774G 7772T 7774T 7772R 7872	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels, Gravix™ tires, foam inserts) (left & right)	2748R 3415 5480X	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TUTTING 168 & TITCATION ROTS Insert, threaded steel (replacement inserts for #7748G, 7748R,
7773 7772G 7774G 7772T 7774T 7772R	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels, Gravix™ tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels,	2748R 3415 5480X	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TUTTINGEROS & TOTELLOS ROSS Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1)
7773 7772G 7774G 7772T 7774T 7772R 7872	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels, Gravix™ tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right)	2748R 3415 5480X 7798	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TITTINGE 165 & TITCATED ROIS Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542T, 8542X)
7773 7772G 7774G 7772T 7774T 7772R 7872	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels, Gravix™ tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right)	2748R 3415 5480X 7798	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TUTHING OS & TITGO FOIS Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542T, 8542X) Toe links, molded composite, 173mm (158mm center to center)
7773 7772G 7774G 7772T 7774T 7772R 7872 7875	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels, Gravix™ tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right)	2748R 3415 5480X 7798 7797 7748	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TITTINICTORS & TITCOLOGIE ROIS Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, molded composite, 173mm (158mm center to center) (black) (2)
7773 7772G 7774G 7772T 7774T 7772R 7872 7875 7876	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels, Gravix™ tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Sledgehammer® tires, foam inserts) (left & right) Tires, Gravix™ (left & right)/ foam inserts (2)	2748R 3415 5480X 7798	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TITTI TOTAL FOR
7773 7772G 7774G 7772T 7774T 7772R 7872 7875 7876 7873 7770X	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels, Gravix™ tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Sledgehammer® tires, foam inserts) (left & right) Tires, Gravix™ (left & right)/ foam inserts (2) Tires, Maxx® AT (left & right) (2)/ foam inserts (2)	2748R 3415 5480X 7798 7797 7748	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TITTILITE LES & TITCATED ROIS Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with
7773 7772G 7774G 7772T 7774T 7772R 7872 7875 7876 7876 7873 7770X 7757	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels, Gravix™ tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Sledgehammer® tires, foam inserts) (left & right) Tires, Gravix™ (left & right)/ foam inserts (2) Tires, Maxx® AT (left & right) (2)/ foam inserts (2) Wheel hex clips (6)	2748R 3415 5480X 7798 7797 7748 7748X	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TITTINITE (195 & TITE 1015 Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7773 7772G 7774G 7774T 7772R 7872 7875 7876 7876 7873 7770X 7757	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels, Gravix™ tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Sledgehammer® tires, foam inserts) (left & right) Tires, Gravix™ (left & right)/ foam inserts (2) Tires, Maxx® AT (left & right)/ foam inserts (2) Wheel hex clips (6) Wheel hubs, hex (2)/ hex clips (2)	2748R 3415 5480X 7798 7797 7748	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TITTINICK S. TITCATER ROIS Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6
7773 7772G 7774G 7774T 7772R 7872 7875 7876 7873 7770X 7756 7756 7756X	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels, Gravix™ tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Sledgehammer® tires, foam inserts) (left & right) Tires, Gravix™ (left & right)/ foam inserts (2) Tires, Maxx® AT (left & right)/ foam inserts (2) Wheel hex clips (6) Wheel hubs, hex, aluminum (blue-anodized) (4)	2748R 3415 5480X 7798 7797 7748 7748X	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TITTINICAGES & TITCAGES FOLION Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends,
7773 7772G 7774G 7774T 7772R 7872 7875 7876 7873 7770X 7757 7756 7756X 7756G	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels, Gravix™ tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Sledgehammer® tires, foam inserts) (left & right) Tires, Gravix™ (left & right)/ foam inserts (2) Tires, Maxx® AT (left & right) (2)/ foam inserts (2) Wheel hubs, hex (2)/ hex clips (2) Wheel hubs, hex, aluminum (blue-anodized) (4) Wheel hubs, hex, aluminum (green-anodized) (4)	2748R 3415 5480X 7798 7797 7748 7748X	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TITTI INCLES & TINCRIENT ROTS Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench,
7773 7772G 7774G 7774T 7774T 7772R 7872 7875 7876 7876 7756 7756 7756X 7756R	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels, Gravix™ tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Sledgehammer® tires, foam inserts) (left & right) Tires, Gravix™ (left & right) foam inserts (2) Tires, Maxx® AT (left & right) (2)/ foam inserts (2) Wheel haus, lex (2)/ hex clips (2) Wheel hubs, hex, aluminum (blue-anodized) (4) Wheel hubs, hex, aluminum (green-anodized) (4) Wheel hubs, hex, aluminum (red-anodized) (4)	2748R 3415 5480X 7798 7797 7748 7748X	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TITTINICAGES & TITCAGES FOLION Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends,
7773 7772G 7774G 7774T 7774T 7772R 7872 7875 7876 7876 7756 7756 7756X 7756R 7758A	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels, Gravix™ tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Sledgehammer® tires, foam inserts) (left & right) Tires, Gravix™ (left & right) / foam inserts (2) Tires, Maxx® AT (left & right) / foam inserts (2) Wheel hubs, hex (2)/ hex clips (2) Wheel hubs, hex, aluminum (blue-anodized) (4) Wheel hubs, hex, aluminum (green-anodized) (4) Wheel hubs, hex, aluminum (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (black-anodized) (4)	2748R 3415 5480X 7798 7797 7748 7748X 7748G	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TITTI INCLES & TITCATICL ROIS Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7773 7772G 7774G 7774T 7774T 7772R 7872 7875 7876 7756 7756 7756X 7756C 7756R 7758A 7758	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels, Gravix™ tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Sledgehammer® tires, foam inserts) (left & right) Tires, Gravix™ (left & right) foam inserts (2) Tires, Maxx® AT (left & right) (2)/ foam inserts (2) Wheel hubs, hex (2)/ hex clips (2) Wheel hubs, hex, aluminum (blue-anodized) (4) Wheel hubs, hex, aluminum (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4)	2748R 3415 5480X 7798 7797 7748 7748X 7748G	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U- joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TITTINIE 16 & Titte 16 Inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum,
7773 7772G 7774G 7774T 7774T 7772R 7872 7875 7876 7756 7756 7756X 7756G 7756R 7758A 7758 7758G	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels, Gravix™ tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Sledgehammer® tires, foam inserts) (left & right) Tires, Gravix™ (left & right)/ foam inserts (2) Tires, Maxx® AT (left & right)/ foam inserts (2) Tires, Maxx® AT (left & right)/ foam inserts (2) Wheel hubs, hex, aluminum (blue-anodized) (4) Wheel hubs, hex, aluminum (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4)	2748R 3415 5480X 7798 7797 7748 7748X 7748G	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TUTTINICK S & TITCAUGI ROIS Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7773 7772G 7774G 7774T 7772R 7872 7875 7876 7876 7756 7756X 7756R 7756R 7758A 7758 7758G 7758G 7758G 7758G 7758G 7758G	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels, Gravix™ tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Sledgehammer® tires, foam inserts) (left & right) Tires, Gravix™ (left & right) foam inserts (2) Tires, Maxx® AT (left & right) foam inserts (2) Wheel hex clips (6) Wheel hubs, hex, aluminum (blue-anodized) (4) Wheel hubs, hex, aluminum (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4)	2748R 3415 5480X 7798 7797 7748 7748X 7748G 7748R	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TUTTINICKIES & TITERIEL ROIS Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) WITCH 12.XX® SUSTIBISTON Kit
7773 7772G 7774G 7774T 7774T 7772R 7872 7875 7876 7876 7756 7756 7756X 7756G 7756R 7758A 7758A 7758B 7758G 7758R	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels, Gravix™ tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Sledgehammer® tires, foam inserts) (left & right) Tires, Gravix™ (left & right)/ foam inserts (2) Tires, Maxx® AT (left & right)/ foam inserts (2) Wheel hex clips (6) Wheel hubs, hex, aluminum (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (black-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4)	2748R 3415 5480X 7798 7797 7748 7748X 7748G	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench / U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TUTTINICK S & TITCALIGIT ROIS Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7773 7772G 7774G 7774T 7772R 7872 7875 7876 7876 7756 7756X 7756R 7756R 7758A 7758 7758G 7758G 7758G 7758G 7758G 7758G	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2) Tires & wheels, assembled, glued (XRT® Race black wheels, Gravix™ tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Maxx® AT tires, foam inserts) (left & right) Tires & wheels, assembled, glued (XRT® Race black wheels, Sledgehammer® tires, foam inserts) (left & right) Tires, Gravix™ (left & right) foam inserts (2) Tires, Maxx® AT (left & right) foam inserts (2) Wheel hex clips (6) Wheel hubs, hex, aluminum (blue-anodized) (4) Wheel hubs, hex, aluminum (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4)	2748R 3415 5480X 7798 7797 7748 7748X 7748G 7748R	Phillips, and #2 Phillips bits), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) Wheel wrench, splined, 17mm TUTTINICKIES & TITERIEL ROIS Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) WITCH 12.XX® SUSTIBISTON Kit

Page 6 X-Maxx®: TQi™ Traxxas Link™ Enabled 2.4GHz Radio & TSM® (Model 77086-4) Parts List

-	
7893	Suspension arm, lower, black (1) (right, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7894X	Suspension arm, lower, blue (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7893X	Suspension arm, lower, blue (1) (right, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7894G	Suspension arm, lower, green (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7893G	Suspension arm, lower, green (1) (right, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7894T	Suspension arm, lower, orange (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7893T	Suspension arm, lower, orange (1) (right, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7894R	Suspension arm, lower, red (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7893R	Suspension arm, lower, red (1) (right, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7892	Suspension arms, upper, black (left or right, front or rear) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7892X	Suspension arms, upper, blue (left or right, front or rear) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7892G	Suspension arms, upper, green (left or right, front or rear) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7892T	Suspension arms, upper, orange (left or right, front or rear) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7892R	Suspension arms, upper, red (left or right, front or rear) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7895	Suspension kit, X-Maxx® WideMaxx®, black (includes front & rear suspension arms, front toe links, driveshafts, shock springs)
7895X	Suspension kit, X-Maxx® WideMaxx®, blue (includes front & rear suspension arms, front toe links, driveshafts, shock springs)
7895G	Suspension kit, X-Maxx® WideMaxx®, green (includes front & rear suspension arms, front toe links, driveshafts, shock springs)
7895T	Suspension kit, X-Maxx® WideMaxx®, orange (includes front & rear suspension arms, front toe links, driveshafts, shock springs)
7895R	Suspension kit, X-Maxx® WideMaxx®, red (includes front & rear suspension arms, front toe links, driveshafts, shock springs)
7897	Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7897A	Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7897X	Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit)
7897G	Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit)
7897R	Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit)
8870R	Fairlead, winch, aluminum (red-anodized) (use with front bumpers #8865, 8866, 8867, 8869, or 9224)

If you have questions or need technical assistance, call Traxxas at:

1-888-TRAXXAS

(1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com

TRAXXAS.COM